

Technical data sheet

DESCRIPTION	DUPLO 30 T		DUPLO 25/2		DUPLO 20/2 T	
Capacity	3.000 kg.	6.608 lbs	2.500 + 2.500 kg.	5.510 + 5.510 kg.	2.000 + 2.000 kg.	4.410 + 4.410 lbs
Standard Lifting Height	2.190 mm	86,2 inch	2.190 mm	86,2 inch	2.190 mm	86,2 inch
Max Lifting Height	2.190 mm	86,2 inch	2.190 mm	86,2 inch	2.190 mm	86,2 inch
Minimum Platform	2200x5200 mm	86.6x204.7 inch	2200x5200 mm	86.6x204.7 inch	2200x5200 mm	86.6x204.7 inch
Standard Platform	2500 x 5200 mm	98.4x204.7 inch	2500 x 5200 mm	98.4x204.7 inch	2500 x 5200 mm	98.4x204.7 inch
Max Platform	2700x5200 mm	106.3x204.7 inch	2700x5200 mm	106.3x204.7 inch	2700x5200 mm	106.3x204.7 inch
Platform distance	2.010 mm	79,1 inch	2.100 mm	82,7 inch	2.010 mm	79,1 inch
Pit	2500 mm	79,1 inch	2500 mm	79,1 inch	2500 mm	79,1 inch
Power	2,6 kw	3,5 hp	2,6 kw	3,5 hp	2,6 kw	3,5 hp
Speed	0,03 m/s	1,2 inch/s	0,03 m/s	1,2 inch/s	0,03 m/s	1,2 inch/s
Power supply	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz
Standard Weight	2850 kg.	6278 lbs	2850 kg.	6278 lbs	2850 kg.	6278 lbs
Notes	tiles on the roof up to 70 kg/m ²	tiles on the roof up to 70 kg/m ²	two platforms for two cars	two platforms for two cars	platform + tiles on the roof up to 70 kg/m ²	platform + tiles on the roof up to 70 kg/m ²