

Technical data sheet

DESCRIPTION	TOTAL REX 30 GOLD		TOTAL REX 30 GOLD F	
Capacity	3000 kg.	6608 lbs	3000 kg.	6608 lbs
Standard Lifting Height	4100 mm	161,4 inch	4100 mm	161,4 inch
Max Lifting Height	4100 mm	161,4 inch	4100 mm	161,4 inch
Minimum Platform	2450X5200 mm	96,5X204,7 inch	2450X5200 mm	96,5X204,7 inch
Standard Platform	2850x5200 mm	112,2x204,7 inch	2850x5200 mm	112,2x204,7 inch
Max Platform	3000x6000 mm	118,1x236,2 inch	3000x6000 mm	118,1x236,2 inch
Net height				
Pit	510 mm	20,1 inch	510 mm	20,1 inch
Power	4 kw	5,5 / 10,2 hp	4 kw	5,5 / 10,2 hp
Speed	0,06 m/s	2,4 inch/s	0,06 m/s	2,4 inch/s
Power supply	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz
Standard Weight	3800 kg.	8370 lbs	4000 kg.	8811 lbs
Notes		tiles on the platform max 70 kg/m ²		tiles on the platform max 70 kg/m ²

DESCRIPTION	TOTAL REX 25 GOLD + T		TOTAL REX 25 GOLD F + T	
Capacity	2500 kg.	5507 lbs	2500 kg.	5507 lbs
Standard Lifting Height	4100 mm	161,4 inch	4100 mm	161,4 inch
Max Lifting Height	4100 mm	161,4 inch	4100 mm	161,4 inch
Minimum Platform	2450X5200 mm	96,5x204,7 inch	2450X5200 mm	96,5x204,7 inch
Standard Platform	2850x5200 mm	112,2x204,7 inch	2850x5200 mm	112,2x204,7 inch
Max Platform	3000x5560 mm	118,1x218,9 inch	3000x5560 mm	118,1x218,9 inch
Net height	2100 mm	82,7 inch	2100 mm	82,7 inch
Pit	510 mm	20,1 inch	510 mm	20,1 inch
Power	5,5 kw	5,5 / 10,2 hp	5,5 kw	5,5 / 10,2 hp
Speed	0,06 m/s	2,4 inch/s	0,06 m/s	2,4 inch/s
Power supply	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz	400 v / 50 hz
Standard Weight	5600 kg.	12335 lbs	5800 kg.	12775 lbs
Notes	tiles on the platform max 70 kg/m ²			